

SHAPES

COLLECTION



Wayne Tile
Company

waynetile.com



WHITE 2x10



WHITE HEXAGON



WHITE 6x16



IVORY WAVE



IVORY 2x10




CREME TEARDROP



CREME WAVE

SHAPES

Creme



2"x10" Field



6"x16" Field



6"x7" Teardrop




4"x8" Hexagon



3"x12" Wave

Ivory



2"x10" Field



6"x16" Field



6"x7" Teardrop



4"x8" Hexagon



3"x12" Wave

White



2"x10" Field



6"x16" Field



6"x7" Teardrop



4"x8" Hexagon



3"x12" Wave

1"x12" Listello Bullnose available in all colors

Características técnicas Technical characteristics

DECLARACIÓN DE PRESTACIONES / DECLARATION OF PERFORMANCE / DÉCLARATION DE PERFORMANCE	
Nº: 002	
1.-	Código de identificación única del producto tipo Unique identification code of the product type Le code d'identification unique du type de produit
Baldosas cerámicas prensadas en seco, con absorción de agua E > 10 % Dry - pressed ceramic tiles, with water absorption E > 10 % Carreaux céramiques pressés à sec, à absorption d'eau E > 10 %	
2.-	Uso o usos previstos Intended use(s) Utilisation(s) prévue(s)
Para paredes interiores For interior walls Pour les murs intérieurs	
3.-	Marca registrada y dirección del fabricante Trade mark and contact address Marque et l'adresse du fabricant
Cerámica Ribesalbes S.A. Ctra. Onda-Ribesalbes, Km. 3,3 12200 Onda (Castellón) - ESPAÑA	
4.-	Sistema de evaluación y verificación de la constancia de prestaciones System of assessment and verification of constancy of performance Système d'évaluation et de vérification de la constance des performances
Sistema 4 / System 4 / Système 4	

Características esenciales Essential Characteristics Caractéristiques essentielles	Prestaciones Performance Performance	Especificación técnica armonizada Harmonized technical specification Spécification technique harmonisée
Reacción al fuego Reaction to fire Réaction au feu	A1 _{FL} / A1	EN 14411:2016
Emisión de sustancias peligrosas Release of dangerous substances Émission de substances dangereuses		
Cadmio Cadmium Cadmium	PND / NPD	
Plomo Lead Plomb	PND / NPD	
Fuerza de rotura Breaking strength Force de rupture	> 1300 N	
Deslizamiento Slip resistance Résistance a la glissance	PND / NPD	
Adhesión Bond strength adhesion Adhésion au mortier de ciment:		
Adhesivo cementoso tipo C1 Cementitious adhesive type C1 Adhésif à base de ciment type C1	> 1 N/mm ²	
Durabilidad para / Durability for / Durabilité pour		
Usos interiores Interior applications Applications intérieures	Cumple / Comply/Conforme	
Propiedades táctiles Tactile properties Propriétés tactiles	PND / NPD	

Cerámica Ribesalbes ha obtenido la Declaración Ambiental de Producto, DAP. Una prueba de su compromiso con la calidad y el respeto al medio ambiente. Este EPD ha sido elaborado y verificado de acuerdo con UNE-EN ISO 14025: 2010 y las Reglas de Categoría de Producto (PCR) indicadas en la tabla 1.

Cerámica Ribesalbes has obtained the Environmental Product Declaration, DAP. This certification is a proof of its quality and respect for the environment. This EPD has been drawn up and verified according to UNE-EN ISO 14025:2010 and the Product Category Rules (PCR) indicated in table 1.

TITLE	Ceramic coverings
REGISTRATION CODE	Global EPD 002-041 rev.1
ISSUE DATE	2018/12/12
CONFORMIDAD	UNE-EN 14411
PROGRAMME	GlobalEPD
PROGRAMME OPERATOR	AENOR